

GENERAL

Sink is formed of #20 gauge, 300 series, nickel-bearing stainless steel. Top mount.

DESIGN FEATURES

Bowl Depth: 8-1/16" (206mm) Rim Height: 3/16" (5mm) Faucet Deck: Raised

Coved Corners: 4" (102mm) vertical and 3-1/4" (83mm) horizontal radius. Finish: Exposed surfaces are polished to an elite satin finish.

OTHER

Drain Opening: 3-1/2" (89mm) Note: Unless otherwise specified, sink is furnished with 4 faucet holes as shown.

Installation Hardware: Included for 3/4" (19mm) countertop.

OPTIONAL ACCESSORIES

Bottom Grid: GBG1415SS

Drain: LK35, D1125

Sink complies with ASME A112.19.3/ CSA B45.4

UPC

Sinks are listed by IAPMO[®] as meeting the applicable requirements of the Uniform Plumbing Code[®], International Plumbing Code[®], and National Plumbing Code of Canada.

SINK PACKAGE

DSE233224DF includes: (1) Sink - DSE233224, (1) Faucet - LK1001CR, and (2) Drains.

DSE233223DFBG includes: (1) Sink - DSE233223, (1) Faucet - LK5000CR, (1) Bottom Grid - GBG1415SS, and (2) Drains.

FAUCET FEATURES

LK1001CR

- Chrome finished, single-lever kitchen faucet with side spray.
- Flexible supply tubes with 1/2" (13mm) male IPS adapters.

LK5000CR

- Chrome finished, single-lever kitchen faucet with pull-down spray.

- Braided stainless steel supply lines.

Faucets comply with: ADA. ANSI/NSF61. ASME A112.18.1/CSA B125.1. cUPC, CA AB1953


Faucet flow rate: 1.5 GPM/5.7 L/min at 60 P.S.I.G.

BOTTOM GRID FEATURES

Nickel-bearing stainless steel Bright finish Dishwasher safe

DRAIN FEATURES

Stainless steel body and strainer. Fits 3-1/2" (89mm) opening.



GBG1415SS




LK5000CR


In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets.

This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

2222 Camden Court Oak Brook, IL 60523









SINK DIMENSIONS (INCHES)*


U. Ohannal	Overall		Inside Each Bowl			Cutout in Countertop (1-1/2"(38mm)		No. of 1-1/2"(38mm)	M : :
U- Channel Model	L	W	L	W	D	Radius Corners)		Dia. Faucet Holes 4"(102mm) Center	Minimum Cabinet
Number	Α	В	С	D	Е	L	W	4 (10211111) Center	Size
DSE23321	33 (838mm)	21-1/4 (540mm)	14 (356mm)	15-3/4 (400mm)	8-1/16 (206mm)	32-3/8 (822mm)	20-5/8 (524mm)	1, 2 , MR2, 3, 4 or 5	36 (914mm)
DSE23322	33 (838mm)	22 (559mm)	14 (356mm)	15-3/4 (400mm)	8-1/16 (206mm)	32-3/8 (822mm)	21-3/8 (543mm)	1, 2 , MR2, 3, 4 or 5	36 (914mm)

*Length is left to right. Width is front to back.




Hole Drilling Configurations 1-1/2" (38mm) Diameter Faucet Holes on 4" (102mm) Centers





E is Bowl Depth

U-Channel Type Mounting System



In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

2222 Camden Court Oak Brook, IL 60523