806-2 Large Diameter

APOLLOPRESS® Press End Copper 45° Street Elbow FTGxC (2-1/2" through 4")

SUBMITTAL SHEET

"Apollo" Flow Controls





Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO#:	
Rep:	
Wholesale Dist.:	

DESCRIPTION

The APOLLOPRESS® 806-2 Large Diameter Press 45° Street Elbow features a lead free dezincification resistant copper body, a patented stainless-steel solid cross-section grab ring, a nylon separation ring and an EPDM o-ring. APOLLOPRESS® products are manufactured utilizing proven ASTM materials and standards. Proudly made in the USA.

FEATURES

- · Lead Free Construction
- Leak Before Press® Technology
- Visual Element, Break Away Band (Pat# 9,532.451)
- Ridgid® XLC Press Tool Compatible
- Made in USA

APPROVALS

- UPC, cUPC & IPC
- IAPMO PS 117-2016 & TIL MSE-13
- NSF/ANSI 61 Water Quality
- · NSF/ANSI 372 Lead Free

PERFORMANCE RATING

- · Maximum Pressure: 300 psi
- Temperature Range: 32°F to 250°F depending on application

APOLLOPRESS®

- · Large Diameter Sizes 2-1/2" through 4"
- Model 806-2, 45° Street Elbow


APOLLOPRESS® connectors are designed for direct mechanical connection to ASTM B88-Type K, L, and M copper tubing in the hard drawn condition. Press connectors are not suitable for steam or flammable gas service.

STANDARD MATERIALS LIST

Body	UNS C12200 Copper				
Grab Ring	316/304 Stainless Steel				
Spacer Ring	Nylon 66				
0-Ring	EPDM				
Lubrication	Silicone, ANSI/NSF-61 Listed				

DIMENSIONS

ITEM NO.	SIZE (IN.)	DIMENSIONS (IN.)								WEIGHT	
HEN NO.		Α	В	С	D	E	F	HEIGHT	WIDTH	DEPTH	(LB.)
10062037	2-1/2	5.97	4.74	1.9	0.91	2.33	3.16	4.74	5.97	3.16	1.34
10062042	3	6.62	5.36	2.1	1	2.48	3.41	5.36	6.62	3.68	1.73
10062047	4	8.18	6.74	2.5	1.51	2.87	4.34	6.74	8.18	4.7	3.53



*LEAD FREE: The wetted surfaces of this product shall contain no more than 0.25% lead by weighted average. Complies with Federal Public Law III-380. ANSI 3rd party approved and listed.

