# 804-2 Small Diameter

APOLLOPRESS® Press End Brass Male Street Adapter FTGxM (1/2" through 2")

# SUBMITTAL SHEET

# "Apollo" Flow Controls





Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO#:	
Rep:	
Wholesale Dist.:	

## **DESCRIPTION**

The APOLLOPRESS® 803-2 Small Diameter Press Male Street Adapter features a lead free dezincification resistant brass body and an EPDM o-ring. APOLLOPRESS® products are manufactured utilizing proven ASTM materials and standards. Proudly made in the USA.

## **FEATURES**

- · Lead Free Construction
- Leak Before Press® Technology
- Ridgid® XL Press Tool Compatible
- · Made in USA

#### **APPROVALS**

- · UPC, cUPC & IPC
- IAPMO PS 117-2016 & TIL MSE-13
- · NSF/ANSI 61 Water Quality
- · NSF/ANSI 372 Lead Free
- IAPMO File Listings: 4861, 6174 & N-4951

# **PERFORMANCE RATING**

- · Maximum Pressure: 300 psi
- Temperature Range: 32°F to 250°F depending on application

## **APOLLOPRESS®**

- · Small Diameter Sizes 1/2" through 2"
- · Model 804-2, Male Street Adapter


APOLLOPRESS® connectors are designed for direct mechanical connection to ASTM B88-Type K, L, and M copper tubing in the hard drawn condition. Press connectors are not suitable for steam or flammable gas service.

#### STANDARD MATERIALS LIST

Body	UNS C27451 Brass				
0-Ring	EPDM				
Lubrication	Silicone, ANSI/NSF-61 Listed				

# **DIMENSIONS**

ITEM NO.	SIZE (IN.)	DIMENSIONS (IN.)						WEIGHT (LB.)
		Α	В	С	HEIGHT	WIDTH	DEPTH	WEIGHT (LB.)
10075816	1/2 FTGxM	2.38	0.84	1.15	0.84	2.38	0.84	0.15
10075822	3/4 FTGxM	2.40	1.05	1.19	1.05	2.4	1.05	0.21
10075826	1 FTGxM	2.50	1.31	1.21	1.31	2.50	1.31	0.33
10075828	1-1/4 FTGxM	2.60	1.66	1.26	1.66	2.60	1.66	0.51
10075830	1-1/2 FTGxM	3.28	1.90	1.70	1.90	3.28	1.90	0.68
10075834	2 FTGxM	3.46	2.37	1.84	2.37	3.46	2.37	0.78



\*LEAD FREE: The wetted surfaces of this product shall contain no more than 0.25% lead by weighted average. Complies with Federal Public Law III-380. ANSI 3rd party approved and listed.

