



CODE	ND	D1	D	Thread	L Thread min	L1	L2	L	H1	H	CH	LCH
27NGF2012NPT (A)	1/2" => 20 mm	0.55	1.46	1/2" NPT	0.53	0.63	1.54	2.11	1.08	1.81	-	-
27NGF2512NPT (A)	3/4" => 25 mm	0.55	1.46	1/2" NPT	0.53	0.67	1.54	2.22	1.20	1.93	-	-
27NGF2534NPT (A)	3/4" => 25 mm	0.73	1.65	3/4" NPT	0.55	0.67	1.54	2.22	1.20	2.03	-	-
27NGF3212NPT (B)	1" => 32 mm	0.55	1.65	1/2" NPT	0.53	0.71	1.81	2.64	1.42	2.24	-	-
27NGF3234NPT (B)	1" => 32 mm	0.73	1.65	3/4" NPT	0.55	0.71	1.81	2.64	1.42	2.24	-	-
27NGF321NPT (B)	1" => 32 mm	0.95	2.13	1" NPT	0.66	0.79	1.81	2.64	1.85	2.91	-	-
27NGF401NPT (B)	1" 1/4 => 40 mm	0.95	2.24	1" NPT	0.66	0.79	2.05	3.11	1.69	2.84	-	-
27NGF50114NPT (C)	1" 1/2 => 50 mm	1.30	2.76	1"1/4 NPT	0.68	0.98	2.60	3.98	2.01	3.39	1.81	0.59
27NGF50112NPT (C)	1" 1/2 => 50 mm	1.56	2.76	1"1/2 NPT	0.68	0.98	2.60	3.98	2.01	3.39	2.17	0.59
27NGF63112NPT (C)	2" => 63 mm	1.56	3.47	1"1/2 NPT	0.68	1.14	3.03	4.76	2.44	4.17	2.17	0.59
27NGF632NPT (C)	2" => 63 mm	1.97	3.47	2" NPT	0.70	1.14	3.23	4.96	2.44	4.17	2.55	0.79



ITEM: NGF_NPT

DESC: FEMALE THREADED 90° ELBOW - W/NPT LEAD FREE BRASS - SOCKET FUSION



DRAWING No:
NI10057

SHEET OF 1 1 REV. -1

www.nupiamericas.com - info@nupiamericas.com

All dimensions have to be considered in inches with 5% tolerance if not otherwise mentioned excluding values as per standard ASTM F2389